

Product Datasheet - 21805

Genesis
ID : 21805
Input power : 50W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire made of gravity die cast aluminium top cover with decorative knob on top, gravity die cast aluminium housing integrated with decorative base leg and base. Die-cast aluminium base suitable for mounting Ø60mm OD pole. Translucent acrylic diffuser formed from non-yellowing acrylic sheet. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 480mm length x 417mm width x 850mm height. CE & BIS Certified. Inhouse NABL accredited lab.
Genesis
ID : 21805
Holder : E27
K-Lite Post top luminaire. Luminaire made of gravity die cast aluminium top cover with decorative knob on top, gravity die cast aluminium housing integrated with decorative base leg and base. Die-cast aluminium base suitable for mounting Ø60mm OD pole. Translucent acrylic diffuser formed from non-yellowing acrylic sheet. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey and Graphite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 480mm length x 417mm width x 850mm height.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey aluminium,RAL 7016 Anthracite grey,Graphite grey