

Product Datasheet - 21807

Dynasty Midi
ID : 21807
Input power : 30W / 50W LED
Technical Description
K-Lite Post top luminaire. 30W / 50W (Symmetrical light distribution) & 50W Type III (Asymmetrical light distribution). Gravity die-cast aluminium top cover with gravity die-cast aluminium decorative knob on top, Die- cast aluminium supporting arm integrated with base suitable for mounting Ø50mm OD pipe. Textured acrylic diffuser / Translucent acrylic diffuser & without diffuser for asymmetrical light. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV-6KV. Luminaire dimension : 325mm square x 545mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Dynasty Midi
ID : 21807
Holder : E27
Technical Description
K-Lite Post top luminaire. Gravity die-cast aluminium top cover with gravity die-cast aluminium decorative knob on top, Gravity die-cast aluminium supporting arm integrated with die-cast aluminium base suitable for mounting Ø50mm OD pole. Textured acrylic diffuser / Translucent acrylic diffuser. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey and Graphite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 325mm square x 545mm height. CE Certified.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: D1

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey