

Product Datasheet - 21809

Ring Fort Arc Micro
ID : 21809
Input power : 30W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire made of specially contoured spun aluminium top cover with die cast aluminium decorative knob on top. Translucent acrylic diffuser. Gravity die-cast aluminium supporting arm with base suitable for mounting Ø38mm OD pipe. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey and Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.90, THD <10%, Surge protection 4KV. Luminaire dimension : 300mm diameter x 550mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Ring Fort Arc Micro
ID : 21809
Holder : E27 Holder
Technical

Description
K-Lite Post top luminaire. Luminaire made of specially contoured spun aluminium top cover with die cast aluminium decorative knob on top. Translucent acrylic / Clear acrylic diffuser. Gravity die-cast aluminium supporting arm with base suitable for mounting Ø38mm OD pipe. All external screws are made of stainless steel. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey and Graphite grey. Prewired with E27 holder and suitable for operating on 240V, 50Hz single phase ac supply. Luminaire dimension : 300mm diameter x 550mm height.

Wattage:

CCT:

Optics:

Mounting: D6

Finish: RAL 9004 Black,RAL 9007 Grey aluminium,RAL 7016 Anthracite grey,Graphite grey