

Product Datasheet - 22527

Wall Cylin Micro
ID : 22527
Input power : 1 x 6W LED / 2 x 6W LED
Technical Description
K-Lite Wall-mounted compact downlight. Beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium (grade 6063) Ø73 x 5mm thickness, Pressure die-cast aluminium glass fixing top & bottom ring of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Polycarbonate optical lens. Single cable entrance M10 cable gland. Pressure die cast aluminium base for surface mounting on wall. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, Surge protection 4KV. Luminaire dimension : 1 x 6W LED - 116mm length x 73mm width x 150mm height / 2 x 6W LED - 116mm length x 73mm width x 180mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 24°,40°,12°

Mounting: W32

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey