

Product Datasheet - 22529

Wall Quad Mini
ID : 22529
Input power : 1 x 6W / 2 x 6W / 1 x 12W / 2 x 12W / 1 x 18W / 2 x 18W LED
Technical Description
K-Lite Wall-mounted compact downlight. Beam angle 12° / 24° / 40°. Luminaire made of extruded aluminium section with inner grooves to fix the top and bottom frame (grade 6063) 100 Square x 3mm thickness, pressure die-cast aluminium glass fixing ring and top closing ring of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 4mm thickness. Polycarbonate optical lens. Single cable entrance via black PG7 cable gland. Pressure die cast aluminium base for surface mounting on wall. Protection class IP65. Mechanical resistance IK07. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, Surge protection 4KV. Luminaire dimension : 1x6W, 1 x 12W, 1 x 18W - 150mm length x 100mm width x 130mm height / 2 x 6W - 150mm length x 100mm width x 210mm height / 2 x 12W, 2 x 18W - 150mm length x 100mm width x 270mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage:

CCT: 2700K,3000K,4000K,6500K

Optics: 24°,40°,12°

Mounting: W32

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey