

Product Datasheet - 22780

lyra Midi
ID : 22780
Input power : 30W LED
Technical Description
K-Lite ceiling mounted compact downlight. Beam angle 12° / 24° / 40°. Luminaire made of spun aluminium, die-cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Aluminium clamp for surface mounting / suspension rod for pendant mounting on ceiling. Polycarbonate optical lens for higher efficiency, lower optical losses with optimum glare suppression. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : Surface - 166mm diameter x 138mm height / Pendant - 166mm diameter x 650mm height. CE Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics: 12°,24°,40°

Mounting: Surface,Pendant

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey