

Product Datasheet - 22793

Beacon Metro Mega 2.0
ID : 22793
Input power : 30W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire body made of pressure die cast aluminium with spun aluminium reflector of high corrosion resistance. Aluminium base suitable for mounting Ø76mm OD pole. Translucent polycarbonate diffuser. All external screws are made of stainless steel. Protection class IP66. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >87%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 410mm diameter x 450mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics: Symmetrical

Mounting: D3

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey