

Product Datasheet - 22808

Luna Midi - Catenary
ID : 22808
Input power : 30W / 50W LED
Technical Description
K-Lite catenary mounted compact street light. Type II / Type III / Type IV (Asymmetrical light distribution). Decorative luminaire made of pressure die cast aluminium body of high corrosion resistance and external non corrosive stainless steel fasteners. Clear toughened glass of 5mm thickness. The module have polycarbonate optical lens. Slight regress in the optical assembly for better glare control. Suitable for mounting on stainless steel rope Ø6mm / Surface. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV / 6KV. Luminaire dimension : 350mm diameter x 127mm height. Inhouse NABL accredited lab.

Wattage:

CCT: 3000K,4000K,5700K

Optics: Type II / Type III / Type IV

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey