

Product Datasheet - 23078

Sill - Facade Luminaire
ID : 23078
Input power : 6W LED
Technical Description
K-Lite high efficiency facade luminaire designed to provide uniform light on the outer ledge of windows creating splendid light effects. Blade Effect (180°) light distribution. Luminaire made of pressure die-cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Polycarbonate optical lens. Die cast aluminium plate for surface mounting. Single cable entrance via M10 cable gland. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Power factor >0.95, THD <10%, Surge protection 2.5KV. Luminaire dimension : 150mm length x 90mm width x 43mm height. CE & BIS Certified. Inhouse NABL certification.

Wattage: 6

CCT: 2700K,3000K,4000K,5700K

Optics: Blade Effect (180°)

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey aluminium, RAL 7016 Anthracite grey,Graphite grey