

Product Datasheet - 23412

Deep
ID : 3412
LED 3000K, 4000K, 5700K 240Vac CRI >80 MacAdam step 3
Input power : Upto 40W
Dimension 1210 x 50 x 70mm
Beam angle : 120°
Electronic driver ON/OFF
CE and BIS

LUMINAIRE TYPE
Linear Light. IP rating IP20
MATERIAL CHARACTERISTICS
High grade aluminium housing (grade 6063 with test certificate) 1200 x 50 x 70mm. Die-cast end cap, Standard suspension kit 1M, Mechanical resistance IK02.
LIGHTING PERFORMANCE
Polycarbonate opal matt diffuser
DEEP
This luminaire contains built-in LED modules. LED modules are engineered accordingly to the existing regulations of Lumen Maintenance (LM80) and Technical Memorandum (TM21), Lifespan of the luminaire > 60,000 hours at 40°C. Operating ambient temperature range is from +25°C to +55°C. Driver efficiency >85%, Power Factor >0.9, THD <10%, Surge protection 3KV.

Wattage:

CCT: 2700K,3000K,4000K,5700K

Optics: 120°

Mounting: Pendant

Finish: RAL 9004 Signal black,RAL 9007 Grey Aluminium,RAL 9016 Traffic White