

Product Datasheet - 24186

Jado 24 - Column Light
ID : 24186
Input power : 1 x 24W LED
Technical Description
K-Lite Column light designed for surface mounted. Asymmetrical light distribution. Luminaire made of rectangular extruded aluminium tube (Grade 6063), pressure die cast aluminium components and non corrosive stainless steel fasteners. Clear acrylic diffuser. MS mounting plate 300mm x 150mm x 12mm thick with 4 elongated holes 38 x 19 to suit M16 bolts at CC 250 x 100 with pure polyester powder coating, Cable entry hole 190 x 40. This mounting plate along with foundation bolts of suitable size to be used for ensuring firm grouting into the specially designed foundation. Protection class IP65. Mechanical resistance IK09. Bamboo / teak finish. Available colour temperature 2700K / 3000K / 4000K / 5700K. Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 2.5KV. Luminaire dimension : 300mm length x 160mm width x 2440mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 24

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: M35

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey