

Product Datasheet - 24352

Cyrilla
ID : 24352
Input power : 12W LED
Technical Description
K-Lite wall luminaire designed for wall mounting. Symmetrical light distribution. Luminaire top cover & bottom frame made of die-cast aluminium (grade ADC12) with extruded aluminium supporting arm (grade 6063). Aluminium base for easy installation onto the wall. Mounting plate square 109 x 10 x 1mm thick with 4 holes Ø5 to suit coach screws at CC 90. All external screws are made of stainless steel. Protection class IP54. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 257mm length x 207mm width x 351mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,6500K

Optics:

Mounting: W28

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey