

Product Datasheet - 24386

Luna
ID : 24386
Input power : 50W / 100W LED
Technical Description
K-Lite Side mounted pole top luminaire. Type II (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Polycarbonate optical lens. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Signal black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 1,00,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Suitable for mounting on to 60mm dia pole. Luminaire dimension : 651mm length x 490mm width x193mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 50W,100

CCT: 3000K,4000K,5700K

Optics: Type II

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey