

Product Datasheet - 24392

Avenue 100
ID : 24392
Input power : 100W LED
Technical Description
K-Lite Side mounted street light luminaire. Type II (Asymmetrical light distribution). Luminaire made of pressure die cast aluminium alloy of high corrosion resistance and non corrosive stainless steel fasteners. Clear toughened glass. Protection class IP66. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. SDCM-3 MacAdam. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.97, THD <10%, Surge protection 6KV. Suitable for mounting on to 60 mm dia pipe at lateral (side entry). Luminaire dimension : 526mm length x 174mm width x 90mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 100

CCT: 2700K,3000K,4000K,5700K

Optics: Type II

Mounting: D2

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey