

Product Datasheet - 24415

Polar - Wall Bracket
ID : 24415
Input power : 50W LED
Technical Description
K-Lite Pole top luminaire. Type III (Asymmetrical light distribution). Luminaire made of extruded aluminium alloy (grade 6063) of high corrosion resistance. Polycarbonate optical lens. Pressure die cast aluminium mounting base for surface mounting on wall. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK09. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 600mm length x 120mm width x 80mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 50

CCT: 2700K,3000K,4000K,5700K

Optics: Type III

Mounting: W33

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey