

Product Datasheet - 24527

Dixon Pro
ID : 24527
Input power : 40W LED
Technical Description
K-Lite Post top luminaire. Beam angle 25°. Luminaire made of extruded aluminium alloy (grade 6063), aluminium top cover with Supporting arms made of gravity die-cast aluminium of high corrosion resistance and non corrosive stainless steel fasteners. Reflector system made of spun aluminium (powder coated white for high reflection). Clear toughened glass. Aluminium base suitable for mounting Ø88.9mm OD pipe. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K. Colour rendering index (CRI)>90. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 770mm diameter x 768mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 40

CCT: 2700K,3000K,4000K,6500K

Optics: 25°

Mounting: D26

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey