

Product Datasheet - 24621

Magnum
ID : 24621
Input power : 200W LED
Technical Description
K-Lite pendant mounted compact street light luminaire. Type II / Type III / Type IV (Asymmetrical light distribution). Luminaire made of die cast aluminium featuring high strength and anti corrosion and non corrosive stainless steel fasteners. Bowl shaped clear polycarbonate diffuser. Suitable for mounting (adjustable from 0°-90° for upside-down and horizontal installation) on tube. Protection class IP65. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 3000K / 4000K / 5700K, Colour rendering index (CRI)>70. K-Lite LED module with expected service life of at least 72,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.95, THD <10%, Surge protection 6KV. Luminaire dimension : 710mm diameter x 545mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 200

CCT: 3000K,4000K,5700K

Optics: Type II,Type III,Type IV

Mounting:

Finish: RAL 9004 Black,RAL 9007 Grey aluminium,RAL 7016 Anthracite grey,Graphite grey