

Product Datasheet - 24625

Cyrilla Pillar
ID : 24625
Input power : 12W LED
Technical Description
K-Lite Pillar Light. Symmetrical light distribution. Luminaire top cover & bottom frame made of die-cast aluminium (grade ADC12) with extruded aluminium supporting arm(grade 6063). Translucent polycarbonate diffuser. Aluminium base for easy installation onto the pillar. Mounting plate square 109 x 10 x 1mm thick with 4 holes Ø5 to suit coach screws at CC 90. All external screws are made of stainless steel. Protection class IP65. Mechanical resistance IK08. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium, RAL 7016 Anthracite grey, Graphite grey. Available colour temperature 2700K / 3000K / 4000K / 6500K, Colour rendering index (CRI)>90. K-Lite LED module with expected service life of at least 60,000 operating hours. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >80%, Power factor >0.95, THD <10%, Surge protection 4KV. Luminaire dimension : 206mm square x 344mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 12

CCT: 2700K,3000K,4000K,6500K

Optics:

Mounting: W28

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey