

Product Datasheet - 24975

Ani
ID : 24975
Input power : 30W LED
Technical Description
K-Lite Post top luminaire. Symmetrical light distribution. Luminaire made of specially contoured spun aluminium top cover with pressure die cast aluminium decorative tightening knob on top. A combination of one on one double diffuser (a clear outer diffuser and a translucent inner diffuser). Die cast aluminium base suitable for mounting Ø50mm OD pipe. All external screws are made of stainless steel. Protection class IP54. Pure polyester powder coated RAL 9004 Black, RAL 9007 Grey aluminium and RAL 7016 Anthracite grey. Available colour temperature 2700K / 3000K / 4000K / 5700K, Colour rendering index (CRI)>80. K-Lite LED module with expected service life of at least 60,000 operating hours. Operating temperature range is from -15°C to +50°C. Prewired with LED driver and suitable for operating on 240V, 50Hz single phase ac supply. Driver efficiency >85%, Power factor >0.90, THD <10%, Surge protection 4KV. Luminaire dimension : 426mm diameter x 322mm height. CE & BIS Certified. Inhouse NABL accredited lab.

Wattage: 30

CCT: 2700K,3000K,4000K,5700K

Optics:

Mounting: D1

Finish: RAL 9004 Black,RAL 9007 Grey Aluminium,RAL 7016 Anthracite Grey,Graphite Grey