K-LiTE

Mila

Mila recess mounted range of LED ceiling lights are a perfect fit for wall washing lighting applications. The die cast aluminium housing is ideal for better thermal management. High lumen output & CCT options make this versatile for indoor lighting solutions. Elegantly designed fixture under the green lighting, energy efficient category.

Product Description

- LED Ceiling recessed mounted tiltable downlight Indoor luminaire with different light beam angles and wattage for varied applications.
- Luminaire made of die-cast aluminium which has excellent mechanical strength, aluminium heat sink for better thermal management.
- Reflector made of anodized aluminium with diffuser made of polycarbonate
- PMMA optical lens is used to provide soft and excellent energy saving performance.
- Cable entries for through-wiring of mains supply cable.
- Suitable for operation on 240V, 50Hz single phase ac supply.
- · Ordering guide: KL-23332 CCT (Colour Temperature)
- Available CCT: 2700K, 3000K, 4000K, 6500K



Product Benefits

- · Quick & simple installation.
- · High performance
- · Sustainable LED technology

Area of Application

Lobbies & Foyers, Retail Sector, Shopping malls, Corridors, Corporate, Residential & Educational premises, Hospitality Industry, Commercial & Business Centers, Conference Center, Restaurants, etc.


Available Finish

White epoxy polyester powder coating.



K-LiTE Mila





Technical Specifications General

ID : 23332 System Wattage : 12W LED Size (mm) : Ø85 x 72

: Ø78 Cutout dimension

Driver Integrated : Constant Current Operating Voltage : 100-277Vac Operating Temperature :-15°C~+50°C

Physical

Body : Die-Cast Aluminium Reflector : Anodized aluminium Diffuser : Polycarbonate Mounting

: Ceiling recess / Fixed Finish : White epoxy polyester

powder coating

Light Source : CITIZEN CRI (Ra) : >80

LED Colour Temperature : 2700K, 3000K, 4000K, 6500K

Driver

Light Source

Power Supply : Integrated Input Voltage : 230-240Vac Frequency : 50-60Hz Power Factor :>0.90 THD :<10% Surge Protection :3KV

:>87% Efficiency Dimmable options : Triac / 1-10V / Dali

