

IVO

Silhouette of the Elegant Shape

Ivo impresses with its up to 2400 mm long elegant housing, bringing you more quality light and cost-savings.

Due to its length and low UGR, it delivers a homogenous and efficient distribution of light. Therefore, it is most suitable for high-end office, supermarkets, conference rooms, office buildings and other spacious environments.

K-LITE

IVO

Power : Upto 20W Upto 40W Upto 80W
 Length: 615mm 1215mm 2415mm



Features

- Nichia LED's
- CRI Ra>80 (>90 On Request)
- SDCM ≤ 3
- L70 / B10 @ 60,000 Hrs



Options

- CCT : 3000K / 4000K / 5700K or TW 2700K to 5700K
- Driver options



L2: Vaccum Metalized Chrome Finish, UGR <12


Beam Angle



RECESS



Dimension in mm



Housing Colour



Extruded aluminium with powder coated finish in
 RAL9005 Black fine texture | RAL9016 White fine texture

Light Distribution refer online



L2 - Direct



L2 - Wall Wash



Technical Specifications

General

Driver	: Constant Current
Input Voltage	: 220-240Vac
Operating Temperature	: -15°C~+50°C

Light Source

Light Source	: Nichia
CRI (Ra)	: >80 (>90 On Request)
LED Colour Temperature	: 3000K / 4000K / 5700K

Optical

Efficiency	: >90%
Tilt	: Fixed
Beam Angle	: 12°, 20°34', 48°, 60°, Wall Wash
Diffuser/Lens Material	: Polycarbonate
Secondary Reflector	: Vacuum Metalized Chrome Finish
UGR	: <12

Physical

Body	: Extruded Aluminium with Die-cast Endcaps
Mounting	: Recess
Finish	: Black(RAL9005) White(RAL9016)

Driver

Power Supply	: Integrated
Power Factor	: >0.90
THD	: <10%
Surge Protection	: Upto 3KV
Efficiency	: >85%



Ordering Guide

Recess

ID	Wattage	C.O.D	Dimension (mm)
3458	Upto 20W	602 x 36	615 x 45 x 50
3459	Upto 40W	1202 x 36	1215 x 45 x 50
3538	Upto 80W	2402 x 36	2415 x 45 x 50

Recess - Wall Wash

ID	Wattage	C.O.D	Dimension (mm)
3487	Upto 20W	602 x 36	615 x 45 x 50
3488	Upto 40W	1202 x 36	1215 x 45 x 50
3539	Upto 80W	2402 x 36	2415 x 45 x 50